

CONWED FIBERS Hydro Mulch 2500 Bonded Fiber Matrix



- CONTROLS EROSION ON THE STEEP SITES IN A QUICK, SAFE EASY HYDRAULIC APPLICATION
- CONTAINS A CROSSLINKED HYDRO-COLLOID TACKIFIER, SUPERABSORBENT CO-POLYMER GEL AND POLY-ACRYLAMIDE THAT FLOCCULATES AND ANCHORS THE FIBER MULCH MATRIX TO THE SOIL SURFACE.
- RETAINS MORE MOISTURE TO IMPROVE TURF ESTABLISHMENT

DIRECTIONS FOR USE

LOAD ACCORDING TO EQUIPMENT
MANUFACTURER'S INSTRUCTIONS. MIX
CONWED FIBERS BFM AT A RATE OF 60 LBS PER
150 GALLONS OF WORKING CAPACITY WATER.



PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +-3
WOOD FIBER	90% MAX
CROSSLINKED TACKIFIER	10% +-1
WATER HOLDING CAPACITY	1350% MIN
ORGANIC MATERIAL	99% +-1
ph	4.8 MIN

TYPICAL APPLICATION RATE

< 3 TO 1 SLOPE	3000 LBS / ACRE
> 1 TO 1 SLOPE	4000 LBS / ACRE

PACKAGING

NET WEIGHT 50 LB BALE, 40 BALES PER PALLET

DISTRIBUTED BY



1697 West 2100 North
Lehi, Utah 84043
801.768.4422 | 801.561.1456
Fax 801.768.3967
info@graniteseed.com
www.graniteseed.com

