

12" Aspen Excelsior Wattles

Erosion logs shall be curled aspen wood excelsior with a consistent width of fibers evenly distributed throughout the log. The casing shall be seamless, photodegradable tube netting and shell conform to the specifications below. The curled aspen wood excelsior shall be fungus-free, resin-free, and shall be free of growth or germination inhibiting substances.



SPECIFICATIONS*

LENGTH..... 10' and 20' Standard

DIAMETER..... 12" (+/- 10%)

CORE..... Aspen Wood Excelsior with Interlocking Barbs
80% Fibers at least 6"

NETTING TYPE..... U.V. Stabilized/Photodegradable
Heavy Duty - 94% High-Density Polyethylene
With 6% UV Inhibitor

NETTING THICKNESS..... Strand Thickness of 0.03"
Knot Thickness of 0.055"

NETTING WEIGHT..... 0.60-Ounce Per Foot

NETTING COLOR..... Black - Other Colors Available as Special Orders

ROLL WEIGHT..... Average 10' - 25lbs
Average 20' - 50 lbs

WEIGHT PER L.F. No Less Than 2.5 lbs

Our Sediment Control Products are used in a multitude of applications, providing benefits such as:

- Better Filtering of Runoff Waters
- Preventing Check Dam Blowouts
- Protecting Water From Going Around Check Dams
- Preventing the Spread of Non-Native Vegetation
- Easier to Handle and Install than Straw Bales
- Safe to use around livestock: non-food source for animals

Distributed By:



1697 West 2100 North
Lehi, Utah 84043
801.768.4422 | 801.561.1456
Fax 801.768.3967
info@graniteseed.com
www.graniteseed.com

*Verified at time of manufacture