







### AEC PREMIER STRAW® (.75) DOUBLE NET MATERIAL SPECIFICATIONS

### **Materials:**

Certified Weed Seed Free Agricultural Straw Polypropylene Netting Stitching Thread

#### **Roll Sizes:**

Width:	8.0 ft (2.4 m)	16.0 ft (4.9 m)
Length:	112.5 ft (34.3 m)	112.5 ft (34.3 m)
Area:	$100.0 \text{ yd}^2 (83.6 \text{ m}^2)$	$200.0 \text{ yd}^2 (167.2 \text{ m}^2)$
Weight:	75.0 lb (34.0 kg)	150.0 lb (68.0 kg)

### **Description:**

AEC Premier Straw Double Net erosion control blanket (ECB) is a natural, stitched straw blanket that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten re-vegetation. AEC Premier Straw Double Net rolls are stretch wrapped to protect against the elements prior to installation, and may be ordered in Master-Paks of fifteen rolls banded together to minimize handling requirements. ECB shall be Manufactured in the U.S.A.

### **Physical Properties:**

Fiber: Certified Weed Seed Free Agricultural Straw Fiber Size: 75% of fibers a minimum of 4" (10.2 cm) long

Weight\*:  $0.75 \text{ lb/yd}^2 (0.41 \text{ kg/m}^2) \pm 10\%$ 

Thread Pattern: No more than 2.0" (5.1 cm) transverse stitch spacing

Net Material: Polypropylene (green with oxo-biodegrader additive or white

with UV degrader additive)

Net Openings: 0.5" wide by 0.5" long (12.7 mm x 12.7 mm)

Net Configuration: Top and bottom



<sup>\*</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of AEC Premier Straw fibers is 15%.









## **MANUFACTURER'S CERTIFICATION**

# **AEC PREMIER STRAW® (.75) DOUBLE NET - Erosion Control Blanket**

#### **Manufacturer:**

American Excelsior Company 831 Pioneer Avenue Rice Lake, WI 54868 1-866-9FIBERS (1-866-934-2377)

<b>Project Information</b> (if applicable)
--

Name:	
<b>Location:</b>	

Number:

#### Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber: Certified Weed Seed Free Agricultural Straw Fiber Size: 75% of fibers a minimum of 4" (10.2 cm) long

Blanket Length: -0' (m), +5% (upon application) Blanket Width: -0" (mm) +1.0" (25.4 mm) Weight\*:  $0.75 \text{ lb/yd}^2 (0.41 \text{ kg/m}^2) \pm 10\%$ 

Thread Pattern: No more than 2.0" (5.1 cm) transverse stitch spacing

Net Material: Polypropylene (green with oxo-biodegrader additive or white

with UV degrader additive)

Net Openings: 0.5" wide by 0.5" long (12.7 mm x 12.7 mm)

Net Configuration: Top and bottom

Rocky Van Gilder V.P. of Wood Operations

03/25/10
Effective Date

**Note:** This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from <a href="https://www.Curlex.com">www.Curlex.com</a> at all times.



<sup>\*</sup> Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of AEC Premier Straw fibers is 15%.